Title: TASER Axon Dock Individual Bay Specifications
Department: Research and Development
Version: 4.1
Release Date: 1/14/2016

Axon Dock Models

Model	Model No.	Color
Axon Dock Individual Bay and Core[1]	70023	Black

Specifications[2]

1. Input power requirements[3]
   Voltage: 15 V DC
   Current: 4 A DC
   Power: 60 W
   Connector: Barrel power connector, inner diameter 0.08″ [2.1 mm], outer diameter 0.22″ [5.5 mm], length 0.37″ [9.5 mm], inside positive
2. Output specifications per port
   Voltage: 4.5 V DC to 5.5 V DC
   Current: 500 mA (maximum)
   Power: 2.75 W (maximum)
3. Operating Temperature: −4 °F [−20 °C] to 167 °F [75 °C]
4. Humidity: 85 percent non-condensing
5. One USB B input port, two 2.5 mm dock output ports, two USB A 2.0 output ports

Characteristics

1. Attaches to Axon Dock core to connect to the Internet.

Features

1. Modular design capable of managing one Axon Flex controller and one Axon Flex camera, or one Axon Body camera and one Axon Flex camera.
2. Status LED on the device docked in the bay indicates device status. Status can also be observed through web-based status screens.
3. Provides power to device docked in the bay to enable battery charging.

Physical Characteristics[2,4]

Width (W)	Height (H)	Depth (D)	Weight
6.4″ [16.2 cm]	2.18″ [5.5 cm]	1.9″ [4.9 cm]	4.76 oz. [135 g]



TOP VIEW



FRONT VIEW



SIDE VIEW



REAR VIEW

[1] This document only describes the bay. For information about the core, see the *TASER Axon Dock Core Specifications*.
[2] Product specification may change without notice; actual product may vary from picture.
[3] Required AC service specifications for provided external AC-DC power supply are 100–240 V AC, 1.5 A (min), 50–60 Hz.
[4] Dimensions and weights are for reference only.

TASER International reserves the right to change this specification without notice.
, AXON, Axon, Axon Body, Axon Flex, TASER, and © are trademarks of TASER International, Inc., some of which are registered in the US and other countries. For more information, visit www.TASER.com/legal. All rights reserved. © 2016 TASER International, Inc.

Title: TASER Axon Dock Core Specifications
Department: Research and Development
Version: 6.0
Release Date: 2/18/2016

AXON

Axon Dock Core Models

Model	Model No.	Color
Axon Dock Core Module	70027	Black

Specifications[1]

1. Input power requirements[2]
   Voltage: 15 V DC
   Current: 4 A DC
   Connector: Barrel power connector, inner diameter 0.08″ [2.1 mm], outer diameter 0.22″ [5.5 mm], length 0.37″ [9.5 mm], inside positive
2. Output specifications per USB Port
   Voltage: 4.5 V DC to 5.5 V DC
   Current: 500 mA (maximum)
   Power: 2.75 W (maximum)
3. Operating Temperature: −4 °F [−20 °C] to 167 °F [75 °C]
4. Humidity: 85 percent non-condensing
5. Two CAT5E[3] Ethernet ports (one 100BASE-TX local area network (LAN[4]), one 1000BASE-T wide area network (WAN))
6. Two USB A 2.0 ports

Characteristics

1. Internet connection requirement:
   Ethernet 10BASE-T (LAN or WAN), 100BASE-TX (LAN or WAN), or 1000BASE-T (WAN)

Features

1. Can be combined with all Axon Dock individual bay and 6-bay modules.
2. Provides secure connection to the Evidence.com[5] website from the device during transfer.
3. Device status can be observed through web-based status screens.
4. Provides power to device connected to the core to enable battery charging.
5. Diagnostic LEDs indicate power, LAN, WAN, and USB activity.
6. Dynamic and static IP capable network connection.
7. TASER web-based configuration interface.
8. Automatic firmware updates for TASER devices.

Physical Characteristics[1,6]

Width (W)	Height (H)	Depth (D)	Weight
6.4″ [16.2 cm]	1.8″ [4.6 cm]	3.31″ [8.4 cm]	8.24 oz. [233.6 g]



[1] Product specification may change without notice; actual product may vary from picture.
[2] Required AC service specifications for provided external AC-DC power supply are 100–240 V AC, 1.5 A (min), 50–60 Hz.
[3] CAT5E cables must be used with the core.
[4] LAN is used for configuring the core. The LAN cannot be used to route network traffic.
[5] Subscription required.
[6] Dimensions and weights are for reference only.

TASER

TASER International reserves the right to change this specification without notice.
AXON, Axon, Evidence.com, TASER, and are trademarks of TASER International, Inc., some of which are registered in the US and other countries. For more information visit www.TASER.com/legal. All rights reserved. © 2016 TASER International, Inc.